

Contreplaqués sur stock

Peuplier

Epaisseurs mm		3	4	5	6.5	7	8	9	10	12	15	16	18	21	22	24	25	27	30	35
Standard	3.1x1.53	●		●			●		●	●	●		●		●		●		●	
	3.1x1.85								●		●		●							
CTBX	3.1x1.53			●					●		●		●							
M1 collage 3	3.1x1.53			●				●					●							

Okoumé

Epaisseurs mm		3	4	5	6.5	7	8	9	10	12	15	16	18	21	22	24	25	27	30	35
Standard	2.5x1.22	●		●			●		●	●	●		●		●		●		●	
	3.1x1.53	●	●	●			●		●	●	●		●		●		●		●	
CTBX	2.5x1.22			●			●		●	●	●		●		●		●		●	
	3.1x1.53			●			●		●	●	●		●		●		●		●	
M1	3.1x1.53			●				●		●	●		●							
Marine	2.5x1.22								●	●	●		●							
Rainuré 1 face	2.5x1.22								●		●									

Cintrable

Epaisseurs mm		3	4	5	6.5	7	8	9	10	12	15	16	18	21	22	24	25	27	30	35
M1 Fil Travers	1.22x2.5							●												
Standard fil Long	2.5x1.22					●		●				●								
Standard fil Travers	1.22x2.5					●		●				●								

Pin Maritime

Epaisseurs mm		3	4	5	6.5	7	8	9	10	12	15	16	18	21	22	24	25	27	30	35
Choix II/III collage extérieur	2.5x1.25									●	●		●							

Faces Bouleau

Epaisseurs mm		3	4	5	6.5	7	8	9	10	12	15	16	18	21	22	24	25	27	30	35
Combi	2.44x1.22										●		●							

